

TECHNICAL SPECIFICATION

POWER OPTIONS

- 4.5kVa Diesel generator

CHASSIS

- Galvanised steel • EEC type approved brakes
- 40mm eye coupling • Sidewinder jockey wheel
- Parking brake

SUSPENSION

- Patented ground lowering air suspension
- Pneumatic • Soft ride

BODY

- Flat zintec panels • Pressed zintec roof
- Rear light guards • Coupling shroud
- Lifting lugs

FINISH

- Semi-gloss paint

DOORS

- 3 anti-vandal doors • 3 point locking system
- Industry standard

WALLS

- Easy clean • Melomine • 50mm insulation

CANTEEN

- Bench seating for 6 people • Under seat storage
- Mains down heater • Running water
- Stainless steel sink • Kettle • Microwave
- Fibreglass worktop • Fibreglass Table
- Freshwater container • Mains lighting
- Window with lockable shutters • Anti-slip flooring

DRYING ROOM

- 6 coat hooks • Mains down heater

WC

- Re-circulating toilet • Fibreglass full arm sink
- Mains lighting • Paper towel dispenser
- Toilet roll holder • Water heater



Cabin from rear



Mains lighting



Running water



Coupling Shroud



Industry standard windows



Industry standard doors



Canteen area